R-4/22/20
MK

EXPRESS - ENCLOSED TRAILERS

COMMERCIAL GRADE
7-10k GVW, TANDEM AXLE

STANDARD EQUIPMENT

FRAME

Rectangle Tubular Steel Construction - Welded All Four Sides
Main Frame Runner 2 x 5 Tubing 1/8" Thick
Crossmember 2 x 3 Tubing 14 Gauge
Tube Uprights 16" On Center (1"x 1" & 1"x 2" 16 Gauge Tubing)
Heavy-Duty Split Rear Doors (1" x 1" 16 Gauge Steel Tubing with 3/8" Exterior Plywood)
Aerodynamic Front & Cambered Roof Design
Jig Welded Frame, Walls, Roof, Front & Doors (Complete Trailer)
Frame is Primed & Painted Black With Oil Base Paint (Electrostatic Process)
2 5/16" Coupler - 14,000 lb Capacity
5,000 lb. Tongue Jack With Sand Pad/Foot
Removable 27" - 10,000 lb. Safety Chains (Class IV)

RUNNING GEAR

7,000 lb. GVW - Two 3,500 lb. Axle With Brakes (Dexter Axle)
10,000 lb. GVW - Two 5,200 lb. Axle With Brakes (Dexter Axle)
Torsion Drop Axles-Rubber / Independent Suspension, Bolt on Application
E-Z Lube Wheel Bearings
Four Wheel Electric Brakes with 12 - Volt Breakaway Kit
15" Radial Trailer Tires ,Load Range "C" for 7k GVW and "D" for 10k. (1 Year No Questions Asked Warra
E-Coated White Modular Wheels (Special Priming Process / Rust Prohibitive)
Stainless Steel Wheel Caps

EXTERIOR

All LED Lighting (Lifetime Warranty), Hermetically Sealed
Molded 7-Way RV Plug
All Aluminum Exterior (.030 Gauge Sheet)
White Aluminum Painted Roof (Apx. 15 Degree Difference In Temp. From Mill Finish)
All Exterior Hardware is Aluminum or Stainless Steel (Hinges, Hasp, Cam Bars)
Aluminum Anti-Racking Cam Bar on Rear Door/Ramp
Aluminum Brush Teardrop Fenders (.080 Gauge)

INTERIOR

3/4" Decking Exterior Grade, B/C Finish (Sealed Underneath with Oil Base Paint)
3/8" Sidewalls Exterior Grade, B/C Finish
Interior LED Dome Light By Each Door
Heavy-Duty Split Rear Doors (1" x 1" 16 Gauge Steel Tubing with 3/8" Exterior Plywood)

Note: above items are subject to change without notice.

COMMON OPTIONAL EQUIPMENT

Rear Ramp Door With Spring Assist
Side Door - 30" , 32" , 36" , 40" , 48" (1" x 1" 16 Gauge Steel Tubing with 3/8" Exterior Plywood)
Side Ramp Door With Spring Assist
V-Nose Style Front Design
Additional Heights
Interior Shelves (Welded Steel Tubing To Wall For Strength, Covered With 3/4" Exterior Plywood)
Roof Vent (1" x 2" 16 Gauged Steel Support Frame)
Spare Tire Mount - Lockable
Triple Weed Eater Racks - Lockable
Blower Hooks & Rack with Tube Holder
12 Exterior Color Choices
Aluminum Diamond Plate Stoneguard 24" High
Aluminum Diamond Plate Corner Guards or Polished Aluminum
Aluminum Roof Ladder Racks (1" x 2" Tube 1/8" Wall)
Aluminum Wheels
Aluminum Ceilings & Walls with Insulation
A/C 15,000/13,500 BTU - With or Without Heat Strip or Heat Pump
E-Track (Welded To Wall For Strength)
Recessed Floor Ties With Backing Plate (4,000 lb Cap.)
Wall Ties (400 lb Cap.)
Motorcycle Chocks (Removable)
Stabilizer Jacks
Beaver/Dove Tail
Electrical Package - 110v
Tandem Axles Lbs. - l2k, l4k,16k & 18/10k Gross Vehicle Weight
Triple Axles Lbs. - l5k, l8k, 21k,24k Gross Vehicle Weight
Concession Awnings / Windows
RV Awnings, Roll Out Style
Interior Fenders

Call For All Other Options